

1.1 **AI.** Human body Tracking Wi-Fi PTZ Camera

Model Number: **50H18WY-S**



1.2 **Stand-out Features**

Support mobile, connectivity, telecommunications and external FDD, WCDMA wireless network, global.

PTZ function

Self-inspection and repair of broken connection: Means when the device can't connect public network, it refreshes every 2 minutes, and automatically reconnect registration dial; (If SIM card does not have flow, automatically check dial after recharging without manual restart)

(In automatic networking mode, if the Wi-Fi and 4G have both automatic setting of Wi-Fi network priorities, and if the Wi-Fi network is detected not be on the Internet, automatically jump to 4G network [Note: Applies To 4G/Wi-Fi Models])

Wi-Fi Mode: you can choose access to Wi-Fi account, input password automatically connected to Wi-Fi network Internet;

INTERNET WIFI function does not require 4G when WIFI is available, it will connect WIFI directly;

Support TF card video, up to 128G;

Hardware configuration:

The standard H. 264 coding chip supports dual code flow technology.;

A SIM card slot to support the three operators network [Note: Applies To 4G/Wi-Fi Models]

One TF card slot, up to 128G;

4 laser lamps, 4 high-power infrared lamps, infrared distance of 250M, 6pcs 5watt LED night vision distance of 100 meters, 2 warning lights (red and blue)
Built-in 5 w power horn/microphone, two-way intercom. Custom voice prompts。

AI multi-point human tracking

● Specification

Model No:	NL6A16-50H18WY-S
sensor	1/2. 8" CMOS
resolution ratio	5.0 Megapixels
signal pattern	NTSC/PAL
Minimum illumination	Color:0.01Lux,B/W:0.001Lux
S/N radio	>60dB
White balance	Auto
Electronic shutter	PAL:1/25~1/100000s NTSC:1/30~1/100000s
Focus length	4. 7~94mm
Optical focus	20X
Focus system	Auto/Manual
Two-way voice	5W Horn, microphone
Presets	100
IR distance	250M
LED light control	Intelligent control technology
LED light angle	Automatic adjustment
Horizontal range	360°Continuous rotation
Vertical range	-90°-0°
Preset call speed	Max 80°/S
Manual call speed	0.01°~80°/S
Network Format	Wifi 2.4ghz
WIFI AP	Support 802.11 b/g/n
antenna	Standard(double antenna)
Cover Distance	Empty 180 M
Shell material	High strength aluminum alloy shell
memory	Support 128G TF card
Working power supply	DC12V/5A
waterproof	IP66 (Both indoor and outdoor)
Installation mode	Walls(optional suspension)
gross weight	5.1KG

Solar power supply system



Specification

Model No.	CSJ-140W70AH
product size	670MM*1200MM
Battery working time	96 hours
Power	DC12V
protection level	IP66
Packing box size	1260*760*200MM
weight	18.5KG
Work temperature	-20℃~60℃
