
T-series Outdoor Station Video Distributor(T-OD) Manual_V1.1




• Introduction In Brief


- 1. This product is created for the extension of 2-wire analog video door phone system, which can expand the amount of Outdoor Stations that are connected in one system.
- 2. Provide amplified output for video signal(transmission gain can be changed by the switch).

Dimension

Outline dimension(L×W×D): 55×55×24 mm



Interface Instruction



Output Port:

Both Bus1 ports are connected in parallel, which can connect with Power Supply, Distributor or Indoor Monitor depend on the actual circumstance.

Input Port:

Bus1, Bus2, Bus3 and Bus4 can connect to Outdoor Station respectively(3 Outdoor Station max).

Switch:

A1: transmission gain 1x. A2: transmission gain 1.2x.

Parameter

No.	Name	Parameters
1	Working Voltage	DC 30V
2	Working Current	≤ 1A (DC 30V)
3	Working Temperature	-10℃~+55℃
4	Storage Temperature	-20℃~+70℃

Attention

- 1. Please keep the devices away from strong magnetic field, high temperature and wet environment.
- 2. Please do not fall the devices to the ground or make them get hard impact.
- 3. Please do not use wet cloth or volatile reagent to wipe the devices.
- Please do not disassemble the devices.